


AD-A167 565 INVESTIGATION OF POLAR MOTION FROM DOPPLER TRACKING OF 1/1
THE MNSS (NAVY NAV. (U) DEFENSE MAPPING AGENCY
HYDROGRAPHIC/ TOPOGRAPHIC CENTER WASHI..
UNCLASSIFIED W H WOODEN ET AL. APR 86

F/G 3/1

NL



MICROCOM[®]

CHART

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE

(1)

Form Approved
OMB No. 0704-0188
Exp. Date: Jun 30, 1985

AD-A167 565

1a. REPORT SECURITY CLASSIFICATION
Unclassified2a. SECURITY CLASSIFICATION AUTHORITY
n/a2b. DECLASSIFICATION/DOWNGRADING SCHEDULE
n/a4. PERFORMING ORGANIZATION REPORT NUMBER(S)

n/a

6a. NAME OF PERFORMING ORGANIZATION

6b. OFFICE SYMBOL
(If applicable)

Defense Mapping Agency

PA

6c. ADDRESS (City, State, and ZIP Code)

Washington, D.C. 20305-3000

8a. NAME OF FUNDING/SPONSORING
ORGANIZATION8b. OFFICE SYMBOL
(If applicable)

DMA Hydrographic/Topographic Ctr

RE

8c. ADDRESS (City, State, and ZIP Code)

Washington, D.C. 20315-0030

11. TITLE (Include Security Classification)

Investigation of Polar Motion from Doppler Tracking of the NNSS During the MERIT Campaign

12. PERSONAL AUTHOR(S)

Wooden, William H., Bangert John A., and J. Milo Robinson

13a. TYPE OF REPORT

13b. TIME COVERED

final

FROM _____ TO _____

16. SUPPLEMENTARY NOTATION

4th International Geodetic Symposium on Satellite Positioning
28 April - 2 May 1986, Austin, Texas

17

COSATI CODES

18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)

FIELD	GROUP	SUB-GROUP
08		

doppler	MERIT Campaign	CELEST
OSCAR	polar motion	NNSS
NOVA	BIH	

19. ABSTRACT (Continue on reverse if necessary and identify by block number)

For more than a dozen years, Doppler tracking of the Navy Navigation Satellite System (NNSS) has demonstrated the ability to give solutions for polar motion as a byproduct of precise ephemerides generation. This paper reviews the polar motion estimation process at the Defense Mapping Agency from Doppler measurements of the NNSS and gives comparisons to polar motion series from newer observational techniques and to the Bureau International de l'Heure (BIH) Circular-D series. The different techniques are compared for the period of the MERIT Main Campaign. In addition to comparing results for the Nova and Oscar NNSS satellites, comparisons are done utilizing the WGS 84 and the NWL 92Z gravitational fields in the precise ephemerides generation process.

Reprints: MERIT Monitor Earth

20. DISTRIBUTION/AVAILABILITY OF ABSTRACT

 UNCLASSIFIED/UNLIMITED SAME AS RPT. DTIC USERS

22a. NAME OF RESPONSIBLE INDIVIDUAL

W. Wooden

21. ABSTRACT SECURITY CLASSIFICATION

UNCLASSIFIED

22b. TELEPHONE (Include Area Code)

202/227-1509

22c. OFFICE SYMBOL

STT

DD FORM 1473, 84 MAR

83 APR edition may be used until exhausted

All other editions are obsolete

SECURITY CLASSIFICATION OF THIS PAGE

UNCLASSIFIED

INSTRUCTIONS FOR PREPARATION OF REPORT DOCUMENTATION PAGE

GENERAL INFORMATION

The accuracy and completeness of all information provided in the DD Form 1473, especially classification and distribution limitation markings, are the responsibility of the authoring or monitoring DoD activity.

Because the data input on this form will be what others will retrieve from DTIC's bibliographic data base or may determine how the document can be accessed by future users, care should be taken to have the form completed by knowledgeable personnel. For better communication and to facilitate more complete and accurate input from the originators of the form to those processing the data, space has been provided in Block 22 for the name, telephone number, and office symbol of the DoD person responsible for the input cited on the form.

All information on the DD Form 1473 should be typed.

Only information appearing on or in the report, or applying specifically to the report in hand, should be reported. If there is any doubt, the block should be left blank.

Some of the information on the forms (e.g., title, abstract) will be machine indexed. The terminology used should describe the content of the report or identify it as precisely as possible for future identification and retrieval.

NOTE: Unclassified abstracts and titles describing classified documents may appear separately from the documents in an unclassified context, e.g., in DTIC announcement bulletins and bibliographies. This must be considered in the preparation and marking of unclassified abstracts and titles.

The Defense Technical Information Center (DTIC) is ready to offer assistance to anyone who needs and requests it. Call Data Base Input Division, Autovon 284-7044 or Commercial (202) 274-7044.

SECURITY CLASSIFICATION OF THE FORM

In accordance with DoD 5200.1-R, Information Security Program Regulation, Chapter IV Section 2, paragraph 4-200, classification markings are to be stamped, printed, or written at the top and bottom of the form in capital letters that are larger than those used in the text of the document. See also DoD 5220.22-M, Industrial Security Manual for Safeguarding Classified Information, Section II, paragraph 11a(2). This form should be unclassified, if possible.

SPECIFIC BLOCKS

Block 1a. Report Security Classification: Designate the highest security classification of the report. (See DoD 5220.1-R, Chapters I, IV, VII, XI, Appendix A.)

Block 1b. Restricted Marking: Enter the restricted marking or warning notice of the report (e.g., CNWDI, RD, NATO).

Block 2a. Security Classification Authority: Enter the commonly used markings in accordance with DoD 5200.1-R, Chapter IV, Section 4, paragraph 4-400 and 4-402. Indicate classification authority.

Block 2b. Declassification / Downgrading Schedule: Indicate specific date or event for declassification or the notation, "Originating Agency Determination Required" or "OADR." Also insert (when applicable) downgrade to _____ on _____ (e.g., Downgrade to Confidential on 6 July 1983). (See also DoD 5220.22-M, Industrial Security Manual for Safeguarding Classified Information, Appendix II.)

NOTE: Entry must be made in Blocks 2a and 2b except when the original report is unclassified and has never been upgraded.

Block 3. Distribution/Availability Statement of Report: Insert the statement as it appears on the report. If a limited distribution statement is used, the reason must be one of those given by DoD Directive 5200.20, Distribution Statements on Technical Documents, as supplemented by the 18 OCT 1983 SECDEF Memo, "Control of Unclassified Technology with Military Application." The Distribution Statement should provide for the broadest distribution possible within limits of security and controlling office limitations.

Block 4. Performing Organization Report Number(s): Enter the unique alphanumeric report number(s) assigned by the organization originating or generating the report from its research and whose name appears in Block 6. These numbers should be in accordance with ANSI STD 239.23-74, "American National Standard Technical Report Number." If the Performing Organization is also the Monitoring Agency, enter the report number in Block 4.

Block 5. Monitoring Organization Report Number(s): Enter the unique alphanumeric report number(s) assigned by the Monitoring Agency. This should be a number assigned by a DoD or other government agency and should be in accordance with ANSI STD 239.23-74. If the Monitoring Agency is the same as the Performing Organization, enter the report number in Block 4 and leave Block 5 blank.

Block 6a. Name of Performing Organization: For in-house reports, enter the name of the performing activity. For reports prepared under contract or grant, enter the contractor or the grantees who generated the report and identify the appropriate corporate division, school, laboratory, etc., of the author.

Block 6b. Office Symbol: Enter the office symbol of the Performing Organization.

Block 6c. Address: Enter the address of the Performing Organization. List city, state, and ZIP code.

Block 7a. Name of Monitoring Organization: This is the agency responsible for administering or monitoring a project, contract, or grant. If the monitor is also the Performing Organization, leave Block 7a blank. In the case of joint sponsorship, the Monitoring Organization is determined by advance agreement. It can be either an office, a group, or a committee representing more than one activity, service, or agency.

Block 7b. Address: Enter the address of the Monitoring Organization. Include city, state, and ZIP code.

Block 8a. Name of Funding/Sponsoring Organization: Enter the full official name of the organization under whose immediate funding the document was generated, whether the work was done in-house or by contract. If the Monitoring Organization is the same as the Funding Organization, leave 8a blank.

Block 8b. Office Symbol: Enter the office symbol of the Funding/Sponsoring Organization.

Block 8c. Address: Enter the address of the Funding/Sponsoring Organization. Include city, state and ZIP code.

Block 9. Procurement Instrument Identification Number: For a contractor grantee report, enter the complete contract or grant number(s) under which the work was accomplished. Leave this block blank for in-house reports.

Block 10. Source of Funding (Program Element, Project, Task Area, and Work Unit Number(s): These four data elements relate to the DoD budget structure and provide program and/or administrative identification of the source of support for the work being carried on. Enter the program element, project, task area, work unit accession number, or their equivalents which identify the principal source of funding for the work required. These codes may be obtained from the applicable DoD forms such as the DD Form 1498 (Research and Technology Work Unit Summary) or from the fund citation of the funding instrument. If this information is not available to the authoring activity, these blocks should be filled in by the responsible DoD Official designated in Block 22. If the report is funded from multiple sources, identify only the Program Element and the Project, Task Area, and Work Unit Numbers of the principal contributor.

Block 11. Title: Enter the title in Block 11 in initial capital letters exactly as it appears on the report. Titles on all classified reports, whether classified or unclassified, must be immediately followed by the security classification of the title enclosed in parentheses. A report with a classified title should be provided with an unclassified version if it is possible to do so without changing the meaning or obscuring the contents of the report. Use specific, meaningful words that describe the content of the report so that when the title is machine-indexed, the words will contribute useful retrieval terms.

If the report is in a foreign language and the title is given in both English and a foreign language, list the foreign language title first, followed by the English title enclosed in parentheses. If part of the text is in English, list the English title first followed by the foreign language title enclosed in parentheses. If the title is given in more than one foreign language, use a title that reflects the language of the text. If both the text and titles are in a foreign language, the title should be translated, if possible, unless the title is also the name of a foreign periodical. Transliterations of often used foreign alphabets (see Appendix A of MIL-STD-8478) are available from DTIC in document AD-A080 800.

Block 12. Personal Author(s): Give the complete name(s) of the author(s) in this order: last name, first name, and middle name. In addition, list the affiliation of the authors if it differs from that of the performing organization.

List all authors. If the document is a compilation of papers, it may be more useful to list the authors with the titles of their papers as a contents note in the abstract in Block 19. If appropriate, the names of editors and compilers may be entered in this block.

Block 13a. Type of Report: Indicate whether the report is summary, final, annual, progress, interim, etc.

Block 13b. Time Covered: Enter the inclusive dates (year, month, day) of the period covered, such as the life of a contract in a final contractor report.

Block 14. Date of Report: Enter the year, month, and day, or the year and the month the report was issued as shown on the cover.

Block 15. Page Count: Enter the total number of pages in the report that contain information, including cover, preface, table of contents, distribution lists, partial pages, etc. A chart in the body of the report is counted even if it is unnumbered.

Block 16. Supplementary Notation: Enter useful information about the report in hand, such as: "Prepared in cooperation with..." "Translation at (or by) ..." "Symposium ..." If there are report numbers for the report which are not noted elsewhere on the form (such as internal series numbers or participating organization report numbers) enter in this block.

Block 17. COSATI Codes: This block provides the subject coverage of the report for announcement and distribution purposes. The categories are to be taken from the "COSATI Subject Category List" (DoD Modified), Oct 65, AD-624 000. A copy is available on request to any organization generating reports for DoD. At least one entry is required as follows:

Field - to indicate subject coverage of report.

Group - to indicate greater subject specificity of information in the report.

Sub-Group - if specificity greater than that shown by Group is required, use further designation as the numbers after the period (.) in the Group breakdown. Use only the designation provided by AD-624 000.

Example: The subject "Solid Rocket Motors" is Field 21, Group 08, Subgroup 2 (page 32, AD-624 000).

Block 18. Subject Terms: These may be descriptors, keywords, posting terms, identifiers, open-ended terms, subject headings, acronyms, code words, or any words or phrases that identify the principal subjects covered in the report, and that conform to standard terminology and are exact enough to be used as subject index entries. Certain acronyms or "buzz words" may be used if they are recognized by specialists in the field and have a potential for becoming accepted terms. "Laser" and "Reverse Osmosis" were once such terms.

If possible, this set of terms should be selected so that the terms individually and as a group will remain UNCLASSIFIED without losing meaning. However, priority must be given to specifying proper subject terms rather than making the set of terms appear "UNCLASSIFIED." Each term on classified reports must be immediately followed by its security classification, enclosed in parentheses.

For reference on standard terminology the "DTIC Retrieval and Indexing Terminology" DRIT-1979, AD-A068 500, and the DoD "Thesaurus of Engineering and Scientific Terms (TEST) 1968, AD-672 000, may be useful.

Block 19. Abstract: The abstract should be a pithy, brief (preferably not to exceed 300 words), factual summary of the most significant information contained in the report. However, since the abstract may be machine-searched, all specific and meaningful words and phrases which express the subject content of the report should be included, even if the word limit is exceeded.

If possible, the abstract of a classified report should be unclassified and consist of publicly releasable information (Unlimited), but in no instance should the report content description be sacrificed for the security classification.

NOTE: An unclassified abstract describing a classified document may appear separately from the document in an unclassified context e.g., in DTIC announcement or bibliographic products. This must be considered in the preparation and marking of unclassified abstracts.

For further information on preparing abstracts, employing scientific symbols, verbalizing, etc., see paragraphs 2.1(n) and 2.3(b) in MIL-STD-8478.

Block 20. Distribution / Availability of Abstract: This block must be completed for all reports. Check the applicable statement: "unclassified / unlimited," "same as report," or, if the report is available to DTIC registered users "DTIC users."

Block 21. Abstract Security Classification: To ensure proper safeguarding of information, this block must be completed for all reports to designate the classification level of the entire abstract. For CLASSIFIED abstracts, each paragraph must be preceded by its security classification code in parentheses.

Block 22a,b,c. Name, Telephone and Office Symbol of Responsible Individual: Give name, telephone number, and office symbol of DoD person responsible for the accuracy of the completion of this form.

INVESTIGATION OF POLAR MOTION FROM DOPPLER TRACKING OF THE
NAVY NAVIGATION SATELLITE SYSTEM DURING THE MERIT CAMPAIGN

WILLIAM H. WOODEN, JOHN A. BANGERT, AND J. MILO ROBINSON
DEFENSE MAPPING AGENCY
WASHINGTON, DC 20305, USA

APR 29 1986

SUMMARY

For more than a dozen years, Doppler tracking of the Navy Navigation Satellite System (NNSS) has demonstrated the ability to give solutions for polar motion as a byproduct of precise ephemerides generation. This paper reviews the polar motion estimation process at the Defense Mapping Agency from Doppler measurements of the NNSS and gives comparisons to polar motion series from newer observational techniques and to the Bureau International de l'Heure (BIH) Circular-D series. The different techniques are compared for the period of the MERIT Main Campaign. In addition to comparing results for the Nova and Oscar NNSS satellites, comparisons are done utilizing the WGS 84 and the NWL 922 gravitational fields in the precise ephemerides generation process.

1.0 INTRODUCTION

Since the late nineteenth century, it has been recognized that the instantaneous spin axis of the Earth moves with respect to the geographic pole of the Earth's crust. This "polar motion" was predicted by Euler in 1752, but was not conclusively observed until Kuenstner's work in 1864-65. The International Latitude Service (ILS) was established in 1893 to continuously monitor the motion of the pole by making systematic determinations of latitude. With the development of new astrometric instruments during the 1950s and their use at the national observatories, it was decided to reorganize the ILS into the International Polar Monitoring Service (IPMS) in 1952 with the charter of deriving polar motion from latitude and universal time data of all astronomical instruments.

The Bureau International de l'Heure (BIH) was created in 1912 to unify time by publishing the time of emission (in universal time) of radio time signals. With the advent of atomic time standards in 1955 and the need to account for polar motion in a timely manner for UT determination, the BIH began to determine its own set of coordinates of the pole from longitude data supplied by participating observatories. Until 1972, the BIH used only the same data as the IPMS so a complete overlap of functions with the IPMS existed. Since 1972, pole positions based on Doppler observations of the Navy Navigation Satellite System (NNSS)

1651

satellites have been incorporated into the BIH global solution. The methods used by the BIH in the treatment of data are given by Feissel [1].

Research at the Naval Weapons Laboratory (now the Naval Surface Weapons Center) by Anderle and Beuglass [2] demonstrated that it was possible to use Doppler observations of NNSS satellites to compute pole positions. Doppler solutions of pole position have been distributed by the Dahlgren Polar Monitoring Service since 1969. The pole positions are a byproduct of the orbit computation process. Hence, when the responsibility of computing the NNSS satellite orbits was transferred to the Defense Mapping Agency (DMA) in 1975, the derivation of pole position was continued by DMA. The DMAHTC Polar Monitoring Service (DPMS) reports are distributed by the Hydrographic/Topographic Center of DMA to users on a weekly or monthly basis.

Project MERIT [3] was a program of international collaboration to monitor Earth rotation and intercompare techniques of observation and analysis. The MERIT Main Campaign of observations was held during the period September 1, 1983, to October 31, 1984 and included a variety of techniques for determining polar coordinates.

2.0 COMPUTATIONAL METHODS FOR DOPPLER DATA

The pole determination method utilized by DMA is the method adopted by the Naval Surface Weapons Center (NSWC) in August 1971. The brief description of the method that follows is taken from the detailed description of the observational procedures and the data reduction techniques given by Anderle [4].

Doppler observations are made daily by a network of approximately 20 worldwide tracking stations controlled by DMA and a network of 4 U.S. tracking stations controlled by the Navy Astronautics Group. All observations taken in a 48-hour period are processed with the CELEST computer program [5]. A least-squares solution is obtained which includes the six constants of orbital integration, a drag scaling factor for each day, a frequency and a tropospheric refraction scaling factor for each pass, the two components of the pole position, and the coordinates of any mobile observing station. The least-squares solution is based on differences between the observations and computed data, which corresponds to a predicted satellite orbit. The initial conditions may be equations of motion come from the previous day's orbit fit. The integration scheme is a 12th-order Cowell with a one-minute stepsize. The mathematical model includes the Earth's gravitational field, atmospheric drag, solar radiation pressure, luni-solar

or	
&	<input checked="" type="checkbox"/>
x	<input type="checkbox"/>
	<input type="checkbox"/>

I	
Availability Codes	
Dist	Avail and/or Special
A-1	24

gravity perturbations, and solid Earth tidal forces. The integration is done in the true-of-date system.

The accuracy of the orbit determination process is reflected by two statistics: the discontinuity in the ephemeris at the ends of each 2-day span and the root mean square of the residuals of the least-squares adjustment process. The current accuracy of the ephemerides is approximately three meters according to Murphy and Fell [6]. This value agrees with the previous values given by Bowman and Leroy [7] and Wooden [8].

During the MERIT Campaign, four NNESS satellites were used at DMAHTC: three "Oscar-type" satellites (DMA 60=1967-92A, DMA 68=1970-67A, and DMA 59=1967-48A) and one "Nova-type" satellite (DMA 105=1981-44A). The Nova satellite is equipped with sensors and thrusters which compensate for non-conservative forces in the direction of the velocity vector. Thus, polar motion results from the Nova satellite are largely unaffected by variations in solar activity.

3.0 ANALYSIS OF DOPPLER POLAR MOTION VALUES

The most important components of polar motion are terms with a Chandler period (420-435 days) and terms with an annual period. The annual motion is believed to be due to seasonal variations such as meteorological effects of changes in air masses over the Earth and changes in vegetation and snow loading. The Chandler motion is a consequence of the fact that the inertial spin of the Earth is about an axis other than its principal axis of inertia.

In an attempt to highlight other geophysical properties or noise motion and instrumental errors between series of Earth orientation parameters, the dominant annual and Chandler motions and a bias were removed by fitting a five-parameter expression of the following form to each component of polar motion:

$$f(t) = A_1 + A_2 \cos \Lambda + A_3 \sin \Lambda + A_4 \cos \Omega + A_5 \sin \Omega \quad (1)$$

where $\Lambda = (2\pi t/365.25)$

$\Omega = (2\pi t/435)$

A_1, A_2, A_3, A_4, A_5 = coefficients of the fit

In the analysis that follows, the two types of NNESS satellites are compared with each other and the SIH Chandler-D values. Special data sets are created for comparison with other Earth orientation parameter series.

3.1. COMPARISON OF OSCAR-TYPE AND NOVA-TYPE NNSS SATELLITES

The differences between the bi-daily values for each individual NNSS satellite and the BIH Circular-D values for the MERIT period are shown in Figure 1. Unfortunately, only the Nova satellite (DMA 105) has observations for the entire MERIT timespan. Although the x and y curves for this satellite have different biases, they show similar behavior with a time offset of approximately 30 days. The x components of Oscar satellites, DMA 59 and DMA 60, tend to follow the Nova satellite curve, while DMA 68 appears to have periodic oscillations about a constant offset. The y components of the Oscar satellites show less variation than the x components. The scatter associated with the Nova satellite values is much smaller than the scatter in the Oscar satellite values. The statistics associated with these comparisons are given in Table 1. The means and standard deviations in the table are in arc seconds. The number of observations is given in the column labeled n. The second set of means and standard deviations in Table 1 are taken from the study by Colquitt, Stein, and Anderle [9].

TABLE 1. STATISTICS FOR THE OSCAR - NOVA COMPARISONS

SERIES	X-MEAN	SIGMA-X	Y-MEAN	SIGMA-Y	N	X-MEAN	SIGMA-X	Y-MEAN	SIGMA-Y
105-BIH	-.009	.015	.007	.015	217				
59-BIH	.005	.016	.007	.013	65				
60-BIH	-.003	.025	.002	.016	103				
68-BIH	-.010	.018	.012	.015	154				
68-60	-.007	.031	.010	.022		-.008	.037	.015	.031
59-60	.008	.024	.004	.021		-.007	.029	.001	.023
105-60	-.006	.023	.005	.022		-.009	.026	.010	.024

In addition to examining the raw observations of the individual satellites, special data sets of 5-day means were created from the individual bi-daily values for the Oscar satellites and for the Nova satellite to make comparisons on the standard pulsar rotation days. These two data sets are designated NOVA and OSCAR. Using these special data sets, the biases and the annual and Chandler motions were removed from the observations by means of Equation 1. Figure 2 gives the differences between the residuals of the fits. The largest differences occur between 200 and 300 days into the MERIT timespan. The statistics associated with these fits will be given in the next section.

3.2. COMPARISON OF OSCAR SATELLITE OBSERVATIONS WITH OTHER EARTH ORIENTATION DATA TYPES

To examine the geophysical information in each Earth orientation series, separate least-squares fits for the x and y components of the position were made using Equation 1

FIGURE 1. DIFFERENCES BETWEEN NNSS AND BIH POLE VALUES





FIGURE 2

NOVA - OSCARS RESIDUAL
PERIODS REMOVED



to remove the annual and Chandler information. The five free parameters of the fits were the mean position of the pole and the amplitudes of the sine and cosine terms of the annual and Chandler motions. Table 2 gives the results of these fits for each data type. The entries of Table 2 are expressed in arc seconds. The BIH series is the Circular-D final values. SLR is the satellite laser ranging series of the University of Texas. VLBI is the Very Long Baseline Interferometry series of the National Geodetic Survey. The SLR and VLBI data were taken from a magnetic tape provided by the US Naval Observatory. DMA is the normal combined solution of weighted means of individual satellites published by DMA on 5-day intervals in the DFMS reports. NOVA and OSCAR are the special 5-day means discussed previously.

TABLE 2. AMPLITUDES OF THE FITTED PARAMETERS

Data Set	x - component					y - component						
	bias	$\cos A$	$\sin A$	$\cos C$	$\sin C$	sigma	bias	$\cos A$	$\sin A$	$\cos C$	$\sin C$	sigma
BIH	.046	.059	-.008	.206	-.093	.008	.282	.014	-.057	-.115	-.178	.006
SLR	.046	.062	-.016	.206	-.083	.010	.272	.012	-.050	-.115	-.185	.007
VLBI	.046	.073	.008	.178	-.107	.006	.277	.004	-.059	-.114	-.180	.006
DMA	.039	.064	.002	.193	-.105	.009	.289	.017	-.059	-.120	-.178	.007
NOVA	.036	.060	.004	.192	-.114	.009	.287	.021	-.051	-.133	-.178	.007
OSCAR	.039	.074	.008	.182	-.108	.013	.289	.019	-.060	-.125	-.179	.010

Figure 3 shows the residuals of the fits whose fitted parameters are given in Table 2. The smooth line in each plot represents a 7-point moving average of the quantity being plotted. As is evident from the figure, the geophysical information is similar for all data types, i.e., the major peaks agree. All the plots of the Y value residuals exhibit a semiannual period although the OSCAR residuals show an extra hump at 200 days. The X component does not exhibit a semiannual period, but has a distinct signature. The differences in the plots occur between 200 and 300 days. BIH and VLBI are relatively flat in that interval, whereas all the other data sets have a small peak. SLR has its peak at 275 days and NOVA has its peak at 230 days. Again the OSCAR residuals are most different with a large peak at 215 days. Faquet, Djurovic, and Techy [10] also note the similarity of the geophysical information in their residual plots.

To further differentiate subtle differences between the Earth orientation parameter series shown in Figure 3, the residuals of the fits were differenced. The results of this process are shown in Figures 4 through 9. Note that Figure 2 presents results of this process for the NOVA and OSCAR series.

FIGURE 3. RESIDUALS OF THE FIVE-PARAMETER FITS FOR THE EOP SERIES




FIGURE 4

OBSRS - BIM RESIDUAL
PERIODS REMOVED





FIGURE 5

IAS - BIM RESIDUAL
PERIODS REMOVED






FIGURE 6

OCEARS - SLR RESIDUAL
PERIODS REMOVED



RESIDUALS (arc seconds)

TIME (days)





FIGURE 7

IOS - SLR RESIDUAL
PERIODS REMOVED



RESIDUALS (arc seconds)

TIME (days)




FIGURE 8
OCRS - VLBI RESIDUAL
PERIODIC REMOVED







FIGURE 9
LSS - VLBI RESIDUAL
PERIODIC REMOVED



4.0 PRELIMINARY EVALUATION OF POLE POSITIONS COMPUTED USING WORLD GEODETIC SYSTEM 1984

Biases between polar motion solutions using different NNSS satellites have been shown to result from uncertainties in knowledge of the Earth's gravity field [11]. The question arises as to whether the development of the World Geodetic System 1984 (WGS 84) and its associated Earth Gravitational Model (EGM), as discussed by Decker [12] and White [13], can improve the pole position solutions. As part of ~~tests of ephemeris generation~~ using WGS 84 (see, for example, [14]), a number of NNSS ephemerides based on WGS 84 have been computed at DMAHTC using the CELEST program. Of particular interest was an interval, beginning in late May and ending in early July 1985, within which WGS 84 precise ephemerides for 5 NNSS satellites were produced on a regular basis. At the same time, analogous precise ephemerides in the NWL 9Z2 system using the NWL 1OE-1 EGM were produced as part of DMAHTC routine production. This situation permitted a preliminary comparison of the pole position solutions computed in the two systems.

4.1 PROCEDURES FOR GENERATING WGS 84 BASED SOLUTIONS

WGS 84 versions of CELEST input files were utilized to produce precise ephemerides of 5 NNSS satellites, from day 149 to day 154 and from day 161 to day 179, in 1985. The program input included the WGS 84 EGM truncated to degree (n) and order (m) 41, as well as the WGS 84 ellipsoid parameters. The program also utilized a file of WGS 84 tracking station coordinates which were obtained by applying a geometric transformation to the "production" NWL 9Z2 coordinates. Each orbit fit for satellites DMA 59, DMA 77, DMA 93, and DMA 113 (Nova) was based on 2 days of tracking data, while each fit for satellite DMA 105 was based on 1 day of data.

During the test period, DMAHTC also produced precise ephemerides of the same 5 NNSS satellites for routine production purposes. These fits utilized the NWL 1OE-1 EGM ($n=29$, $m=27$) and the NWL 9Z2 tracking station coordinate set. Data editing occurred independently in the analogous CELEST solutions in the two systems (i.e., no attempt was made to enforce common data between the solutions).

The pole coordinates output in the two systems were compared to BIH Circular-0 values of x and y . Daily values were derived from the BIH 5-day values by cubic spline interpolation, and differences were formed between the interpolated values and the Doppler-derived values. These differences were computed in the sense Doppler minus BIH. The pole position solutions which resulted from the

Table 3: Statistics of the Differences Between the Doppler-Derived Pole Coordinates and the BIH Pole Coordinates

SAT.		Δx (arcsec)		Δy (arcsec)	
		NWL 922	WGS 84	NWL 922	WGS 84
59 n=11	$\bar{\Delta}$	+ .0020	+ .0147	+ .0218	+ .0242
	σ	$\pm .0239$	$\pm .0264$	$\pm .0180$	$\pm .0195$
77 n=13	$\bar{\Delta}$	- .0016	+ .0120	+ .0191	+ .0195
	σ	$\pm .0215$	$\pm .0189$	$\pm .0193$	$\pm .0182$
93 n=11	$\bar{\Delta}$	+ .0304	+ .0342	+ .0269	+ .0256
	σ	$\pm .0123$	$\pm .0155$	$\pm .0094$	$\pm .0154$
105 n=21	$\bar{\Delta}$	+ .0138	- .0053	- .0032	+ .0048
	σ	$\pm .0162$	$\pm .0101$	$\pm .0113$	$\pm .0107$
115 n=13	$\bar{\Delta}$	+ .0160	+ .0068	+ .0374	+ .0180
	σ	$\pm .0189$	$\pm .0138$	$\pm .0198$	$\pm .0063$

Table 4: Statistics of Pole Coordinate Differences Grouped By NNSS Types

Satellite Type		Δx (arcsec)		Δy (arcsec)	
		NWL 922	WGS 84	NWL 922	WGS 84
OSCARs (59,77,93) n=35	$\bar{\Delta}$	+ .0096	+ .0198	+ .0224	+ .0229
	σ	$\pm .0241$	$\pm .0224$	$\pm .0163$	$\pm .0175$
NOVAs (105,115) n=34	$\bar{\Delta}$	+ .0147	- .0007	+ .0123	+ .0099
	σ	$\pm .0170$	$\pm .0129$	$\pm .0250$	$\pm .0112$

Notes: $\bar{\Delta}$ = mean difference

σ = standard deviation

n = number of orbit fits

satellite DMA 105 fits (in both systems) on day 175 were outliers and were rejected from further study.

4.2 PRELIMINARY RESULTS OF WGS 84 - BASED POLE SOLUTIONS

Table 3 presents statistics of the differences between the BIH and the Doppler-derived pole coordinates on a satellite-by-satellites basis. An examination of this table gave no conclusive evidence that use of WGS 84 systematically improved the agreement between the Doppler-derived values and the BIH values. However, when the satellites were grouped by type (i.e., Nova and Oscar), as in Table 4, a possible correlation emerged. While the pole positions determined using the Oscar satellites and WGS 84 showed no improvement in agreement with the BIH values, pole positions determined using the Nova satellites and WGS 84 did show better agreement with BIH. Additionally, there was less scatter in the Nova differences when WGS 84 was utilized, as evidenced by the smaller standard deviations.

5.0 CONCLUSIONS

The polar motion derived from Doppler tracking of the NNESS satellites has provided and continues to provide valuable Earth orientation information. When the annual and Chandler components of polar motion are removed from the observational data of each Earth orientation series, the same geophysical information remains. Nova-type NNESS satellites provide more precise estimates of pole position than Oscar-type NNESS satellites. Preliminary analysis shows that the use of WGS 84 may improve the accuracy of the pole positions derived from the Nova satellite orbit fits, but that its use for Oscar satellites does not lead to improved accuracies. However, more data need to be processed to substantiate these preliminary results.

6.0 ACKNOWLEDGMENTS

It is a pleasure to thank Drs. D. McCarthy and A. Babcock for providing a tape of SLR and VLBI polar motion data used for these comparisons with Doppler-derived data. The authors also wish to acknowledge the contributions of Mr. J. Synnefakis, who computed the WGS 84 test ephemerides, and Mr. F. Mueller, who compiled the pole solutions and computed the statistics for Section 4 of this paper.

7.0 REFERENCES

1. Feissel, M., "Determination of the Earth Rotation Parameters by the Bureau International de l'Heure, 1962-1979", Bulletin Geodesique, 54, 81, 1980.
2. Anderle, R. J. and L.K. Beuglass, "Doppler Satellite Observations of Polar Motion," Bulletin Geodesique, 96, 125, 1970.
3. Wilkins, G.A. (ed.), "Project MERIT, IAU-IUGG Joint Working Group on the Rotation of the Earth," Royal Greenwich Observatory, Herstmonceux Castle, England, 1980.
4. Anderle, R.J., "Determination of Polar Motion from Satellite Observations," Geophysical Surveys, 1, 147, 1973.
5. O Toole, J.W., "CELEST Computer Program for Computing Satellite Orbits," Naval Surface Weapons Center TR-3565, 1976.
6. Murphy, J.K. and P.J. Fell, "DMA Orbit Determination for Transit Satellites: 1985," Proc. Fourth Int. Geodetic Symposium, Austin, Texas, 1986.
7. Bowman, B.R. and C.F. Leroy, "DMATC Doppler Determination of Polar Motion," Proc. Int. Geodetic Symposium, Las Cruces, New Mexico, 1, 141, 1976.
8. Wooden, W.H., "A Comparison of Pole Positions Derived from GPS Satellite and Navy Navigation Satellite Observations," Proc. Third Int. Geodetic Symposium, Las Cruces, New Mexico, 1, 71, 1982.
9. Colquitt, E.S., W.L. Stein, and R.J. Anderle, "Doppler Polar Motion Measurements During Project MERIT," Int. Symp. on Space Techniques for Geodynamics, Szeged, Hungary, 1984.
10. Paquet, P., D. Djurovic, and G. Techy, "Agreement in Polar Motion Measurements During the MERIT Campaign," Proc. Int. Conf. Earth Rotation and Terrestrial Ref. Frame, Columbus, Ohio, 2, 656, 1985.
11. Colquitt, E., et al., "Bias in Pole Positions Computed from Navy Navigation Satellites," presented at AAS/AIAA Astrodynamics Specialist Conference, Lake Tahoe, Nevada, 1981.
12. Becker, B.L., "World Geodetic System 1984," Proc. Fourth Int. Geodetic Symposium, Austin, Texas, 1986.
13. White, P.L., "The World Geodetic System 1984 Earth Gravitational Model," Proc. Fourth Int. Geodetic Symposium, Austin, Texas, 1986.

14. Cunningham, J., C.W. Malyevac, R. Whitesell, and S. Malys, "Testing of the World Geodetic System 1984 in Precise Orbit Determination and Point Positioning," Proc. Fourth Int. Geodetic Symposium, Austin, Texas, 1986.

TEXAS